



CanSlip SE

Use and Care Spray Stand

Use CanSlip SE to: Help prevent asphalt sticking to truck boxes.

Using CanSlip SE:

- ◆ Mix 1 part CanSlip SE to 10 parts of water.
- ◆ Best working temperature range is 5°C to 50°C

Stand Setup	Spraying Truck Boxes
<ul style="list-style-type: none"> ◆ Venturi injectors and other equipment used to dilute the product should only be adjusted by plant manager or authorized persons. ◆ Do not allow rainwater to leak into the drum of CanSlip SE concentrate. 	<ul style="list-style-type: none"> ◆ Special attention should be given to the corners of the truck bed. ◆ Release agent is normally applied at the beginning of the shift and is effective for up to three loads before re-spraying is required.

To Ensure Effectiveness	Cautionary Measures
<ul style="list-style-type: none"> ◆ Spray mixture sparingly – one litre per truck bed. ◆ Over-spraying lowers the effectiveness. ◆ Emulsion leaves protective oily film when the water evaporates. ◆ MultiSolv “HotHut” enclosures can be used to keep product at working temperature in cooler weather conditions. ◆ CanSlip Late Season can also be used effectively in lower temperatures. 	<ul style="list-style-type: none"> ◆ Exercise care when spraying in windy conditions. Fine mist is an inhalation hazard. ◆ Product can make spray stands and hoses slippery if not removed from surfaces. ◆ Product soaked cloths are a potential fire hazard and should be stored in approved containers.